



ESGARD FLANGE KOTE

DESCRIPTION	A mastic formula specifically designed to fill the annular between two fastened flanges. Esgard Flange Kote will not bleed, dry, or crack with age.
FIELD OF APPLICATION	Flanges.

TECHNICAL DATA

TYPE	Rust-inhibitive compound.
DENSITY	9.57 lb/gal (1/15 kg/l)
VISCOSITY	NLGI Grade 1 (one) grease
VOLUME SOLIDS	100%
FLASH POINT	325°F (163°C) COC

SURFACE PREPARATION Remove loose rust, dirt, oil, grease and standing water via the most economical method.

APPLICATION Apply Flange Kote through an Esgard Flange Band with a grease gun designed to fit a 5 gallon pail. Do not thin or dilute. Several types are as follows:

- Manual: Model 1292 (Lincoln)
Model 854 (Balcrank)
- Pneumatic: Model 989 (Lincoln)
Model 754 (Balcrank)

CLEAN UP Esgard Thinner 102. Personal clean up with soap and water.

ORDERING INFORMATION

CONTACT # 1-800-888-2511

	<u>1 GAL</u>	<u>5 GAL</u>
Flange Kote	11.0 lb (5.0 kg)	48.0 lb (21.9 kg)
Thinner 102	7.5 lb (4.3 kg)	35.5 lb (16.1 kg)

Manufacturers of Quality Paints, Protective Coatings, and Lubricants
 Esgard, Inc. 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
 (337) 234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgard.com



FLASH POINT

Flange Kote	325°F (163°C)
Thinner 102	107°F (42°C)

COLORS

Grey. Custom colors on request.

SHELF LIFE

Twelve (12) months from date of shipment.

CAUTION

FOR INDUSTRIAL USE ONLY! Contains petroleum oils. **DO NOT USE OR STORE NEAR HEAT, SPARKS, OR FLAMES.** Close container after use.

SAFETY:

Refer to material safety data sheet supplied with each order

FIRST AID

Refer to Material Safety Data Sheet supplied with each order.