



ESGARD HEAVY DUTY GEAR & PINION LUBE

DESCRIPTION	Esgard Heavy Duty Gear & Pinion Lube is a quality gear dressing designed for open gear system which requires lubrication with superior rust prevention. Esgard Heavy Duty Gear & Pinion Lube will not dry crack, crack or bleed with age and will not drop up to 325°F (163°C).
FIELD OF APPLICATION	Open gears, racks and pinions of offshore jack-up rigs, cranes, etc.

TECHNICAL DATA

FILM PROPERTIES	Dark metallic gray compound that contains no heavy metals and does not dry, crack or bleed. It contains active rust inhibitors and molydisulfide for friction reduction.
TYPE	Rust-inhibitive compound.
DENSITY	11.1 lb/gal (1.33 kg/l)
VISCOSITY	NLGI Grade 1 (one) grease
VOLUME SOLIDS	100%

APPLICATION	Apply by hand, swab or brush directly from container. If removal is desired, use any hydrocarbon solvent. Do not thin or dilute.
--------------------	--

ORDERING INFORMATION

CONTACT #	1-800-888-2511	
SHIPPING WEIGHT	<u>5 GAL</u>	<u>55 GAL</u>
FLASH POINT	HDG&PL 58.5 lb (26.6 kg)	620.0 lb (281.8 kg)
	HDG&PL	325°F (163°C) COC
SHELF LIFE	Two (2) years from date of shipment.	

CAUTION **FOR INDUSTRIAL USE ONLY!** Contains petroleum oils. **DO NOT USE OR STORE NEAR HEAT, SPARKS, OR FLAMES.** Close container after use.

SAFETY: Refer to material safety data sheet supplied with each order

FIRST AID Refer to Material Safety Data Sheet supplied with each order.

Manufacturers of Quality Paints, Protective Coatings, and Lubricants
 Esgard, Inc. 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
 (337) 234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgard.com