



CABLEGARD WIRE ROPE & CABLE SERVICE DRESSING

DESCRIPTION	<i>Esgard CableGard Wire Rope & Cable Service Dressing</i> is a wire rope and cable dressing specifically designed for field service application to extend the life of wire rope and cable. <i>Esgard CableGard</i> conforms to Esgard's high standards, specifically lubricating against wear, displacing moisture, resisting washout by penetrating the cable, and preventing rust and corrosion. <i>Esgard CableGard</i> contains no solvents, requires no heating for application, and will not dry out or crack with age. <i>Esgard CableGard does not produce a sheen when immersed. Esgard CableGard</i> performs at the upper end of specialty, high performance greases/grease-type products.
FIELD OF APPLICATION	All field service application of wire ropes of all types, anchor lines, pendant lines, guy wires, cranes

TECHNICAL DATA

TYPE	Rust- inhibitive compound.	DENSITY	13.6 lb/gal (1.63 kg/l)
VISCOSITY	NLGI Grade 2 (Two)	CONE PENETRATION	269 mm
TEXTURE	Creamy and smooth	VOLUME SOLIDS	99.97%
DROPPING POINT	> 550°F (288°C)	VOLATILE MATTER	0.03%
FLASH POINT	294°F (145.5°C)	SALT FOG (ASTM B117)	Pass (4500 hrs)
LOAD WEAR INDEX (ASTM 2596)	91.2	WELD LOAD	500 kg

APPLICATION Apply by swabbing, brushing, or under pressure through a wire rope lubricator. Contact *Esgard* for specific lubricator recommendations. *Esgard CableGard* comes ready to use. Do not thin or dilute.

ORDERING INFORMATION

CONTACT # 1-800-888-2511

Manufacturers of Quality Protective Coatings
Esgard, Inc. 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com



SHIPPING WEIGHT		<u>5 GAL</u>	<u>55 GAL</u>
	<i>Esgard CableGard</i>	71.0 lb (32.36 kg)	727.0 lb (330.8 kg)
FLASH POINT	<i>Esgard CableGard</i>	294°F (145.5°C) COC	
SHELF LIFE	Two (2) years from date of shipment.		
CAUTION	FOR INDUSTRIAL USE ONLY! Contains petroleum oils. DO NOT USE OR STORE NEAR HEAT, SPARKS OR FLAMES. Close container after use.		
SAFETY/FIRST AID	Refer to Material Safety Data Sheet supplied with each order.		