



INTER KOTE

DESCRIPTION	Esgard Inter Kote is a specific oil based formulation for the internal protection of tubular goods against rust and corrosion while in storage. Inter Kote is specially designed to prevent coating accumulation whereby close tolerance tools may be run without danger of a “gumming” or ‘plugging” effect.
FIELD OF APPLICATION	Tubing, casing, drill pipe, drill collars, line pipe and prefabricated meter runs

TECHNICAL DATA

TYPE	Modified rust – inhibitive petroleum oil
V.O.C.	0 lb/gal (0 g/l)
VOLUME SOLIDS	100%
DENSITY	7.69 lb/gal (0.9 kg/l)
RECOMMENDED DRY FILM THICKNESS	3.0 - 4.0 mils (75 - 100 microns)

SURFACE PREPARATION Remove scale and dirt by internal rattling or wire brushing, and blow out debris with compressed air.

APPLICATION **DO NOT THIN. APPLY AS DELIVERED.** Apply coating with either conventional or airless equipment to a wet film thickness of 3.0 – 4.0 mils (75 – 100 microns).

CLEAN UP Esgard Thinner 101 or xylene. For personal cleanup, use soap and water.

ORDERING INFORMATION

CONTACT #	1-800-888-2511
SHIPPING WEIGHT	<u>55 GAL</u>
	Inter Kote 459.0 lb (208.4kg)
FLASH POINT	Inter Kote 355°F (179°C)

Manufacturers of Quality Paints and Protective Coatings
Esgard, Inc. . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgard.com



SHELF LIFE Thirty-six (36) months from date of shipment.

CAUTION **FOR INDUSTRIAL USE ONLY!** Contains petroleum distillates. **DO NOT USE NEAR HEAT, SPARKS, OR FLAMES.** Close container after use.

SAFETY Refer to Material Safety Data Sheet supplied with each order.

FIRST AID Refer to Material Safety Data Sheet supplied with each order.