



r.

ESGARD RUST CONVERTER

DESCRIPTION	Rust Converter is a liquid zinc phosphate solution that promotes corrosion inhibition and converts red rust (ferrous oxide) to the more stable black rust (ferric oxide). Product advantages include: <ol style="list-style-type: none">1. Treated surfaces need not be washed or cleaned again prior to paint application.2. No powdery residue.3. No latex resins to interfere with adhesion of applied coatings.
FIELD OF APPLICATION	For use on ferrous metal surfaces to stabilize any remaining red rust on hand or power tool cleaned surfaces prior to paint application.

TECHNICAL DATA

TYPE	Zinc oxide/Phosphoric acid solution
V.O.C.	0.81 lb/gal (97 g/l)
DENSITY	9.79 lb/gal mixed (1.17 kg/l)
DRY TIME	3 - 5 hours @ 77°F (25°C) 80% R.H.

SURFACE PREPARATION	Thoroughly clean any oil or grease contaminated areas. Remove all rust scale to expose sound base metal using the most economical methods.
APPLICATION	Apply full strength from a non-metallic container by brushing or swabbing to thoroughly wet the surfaces. Allow to dry completely before painting.
CLEAN UP	Use soap and water.

ORDERING INFORMATION

CONTACT #	1-800-888-2511	
SHIPPING WEIGHT	<u>1 GAL</u>	<u>5 GAL</u>
	Rust Converter	10.1 lb (4.6 kg) 52.0 lb (23.6 kg)
FLASH POINT	Not applicable.	
COLORS	Clear	
SHELF LIFE	Twelve (12) months from date of shipment.	



CAUTION

FOR INDUSTRIAL USE ONLY! CORROSIVE! Contains phosphoric acid and nitric acid.

SAFETY/FIRST AID:

Refer to material safety data sheet supplied with each order