



THREAD KOTE

DESCRIPTION	Esgard Thread Kote is a quality thread coating for long term protection of tubular goods against rust and corrosion while in storage. Thread Kote resists drying, bleeding, or cracking with age and will remain as applied new for the duration of storage. Thread Kote contains NO heavy metals such as zinc, lead, or chromates.
FIELD OF APPLICATION	Tubing, casing, drill pipe, drill collars, line pipe (beveled edges)

TECHNICAL DATA

TYPE	Highly rust – inhibitive compound
DENSITY	9.10 lb/gal (1.09 kg/l)
DROPPING POINT	325°F (163°C)
COLOR	Assorted colors available

SURFACE PREPARATION	Clean threads with a suitable solvent to remove old thread compounds and grease.
APPLICATION	<u>DO NOT THIN. APPLY AS DELIVERED.</u> Apply Thread Kote with a brush or swab.
CLEAN UP	Esgard Thinner 102 or mineral spirits. For personal cleanup, use soap and water.

ORDERING INFORMATION

CONTACT #	1-800-888-2511		
SHIPPING WEIGHT	<u>5 GAL</u>	<u>55 GAL</u>	
	Thread Kote	48.5 lb (22.0kg)	541.0 lb (245.9kg)
FLASH POINT	Thread Kote	325°F (163°C)	

Manufacturers of Quality Protective Coatings
Esgard, Inc. . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com



SHELF LIFE	Thirty-six (36) months from date of shipment.
CAUTION	FOR INDUSTRIAL USE ONLY! Contains petroleum distillates. DO NOT USE NEAR HEAT, SPARKS, OR FLAMES. Close container after use.
SAFETY	Refer to Material Safety Data Sheet supplied with each order.
FIRST AID	Refer to Material Safety Data Sheet supplied with each order.

Manufacturers of Quality Protective Coatings
Esgard, Inc. . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com