



VARNI KOTE H.S.

DESCRIPTION	Esgard Varni Kote H.S. is a high solids industrial grade protective varnish for protection of tubular goods against rust and corrosion while in storage. Varni Kote H.S. yields a hard, yet flexible, clear glossy film.
FIELD OF APPLICATION	Tubing, casing, drill pipe, drill collars, and line pipe

TECHNICAL DATA

TYPE	Synthetic resin solution
V.O.C.	4.22lb/gal (506 g/l)
DENSITY	8.3 lb/gal (1.0 kg/l)
RECOMMENDED DRY FILM THICKNESS	3.0 - 4.0 mils (75 - 100 microns)
DRY TIME @ 3 MILS DFT, 77°F (27°C) 65% R.H.	To touch: 5 minutes To handle: 30 minutes

SURFACE PREPARATION Remove rust, dirt, hydrocarbon deposits, etc. through the use of hand or mechanical means. .

APPLICATION **DO NOT THIN. APPLY AS DELIVERED.** Apply coating with either conventional or airless equipment to a dry film thickness of 3.0 – 4.0 mils (75 – 100 microns).

CLEAN UP Esgard Thinner 101 or xylene. For personal cleanup, use soap and water.

ORDERING INFORMATION

CONTACT # 1-800-888-2511

Manufacturers of Quality Protective Coatings
Esgard, Inc. . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com



SHIPPING WEIGHT		<u>55 GAL</u>
	Varni Kote H.S.	470.0 lb (213.8kg)
FLASH POINT	Varni Kote H.S.	80°F (27°C)
SHELF LIFE	Eighteen (18) months from date of shipment.	
COLORS	Clear and black tint	
CAUTION	FOR INDUSTRIAL USE ONLY! FLAMMABLE! Contains petroleum distillates. DO NOT USE NEAR HEAT, SPARKS, OR FLAMES. Close container after use.	
SAFETY	Refer to Material Safety Data Sheet supplied with each order.	
FIRST AID	Refer to Material Safety Data Sheet supplied with each order.	

Manufacturers of Quality Protective Coatings
Esgard, Inc. . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com