



VARNI KOTE

DESCRIPTION	Esgard Varni Kote is a fast drying industrial grade protective varnish for protection of tubular goods against rust and corrosion while in storage. Varni Kote yields a hard, yet flexible, clear glossy film.
FIELD OF APPLICATION	Tubing, casing, drill pipe, drill collars, and line pipe

TECHNICAL DATA

TYPE	Synthetic resin solution
V.O.C.	4.66lb/gal (559 g/l)
DENSITY	7.16 lb/gal (0.86 kg/l)
RECOMMENDED DRY FILM THICKNESS	3.0 - 4.0 mils (75 - 100 microns)
DRY TIME @ 3 MILS DFT, 77°F (27°C) 65% R.H.	To touch: 5 minutes To handle: 30 minutes

SURFACE PREPARATION	Remove rust, dirt, hydrocarbon deposits, etc. through the use of hand or mechanical means. .
----------------------------	--

APPLICATION	<u>DO NOT THIN. APPLY AS DELIVERED.</u> Apply coating with either conventional or airless equipment to a dry film thickness of 3.0 – 4.0 mils (75 – 100 microns).
--------------------	--

CLEAN UP	Esgard Thinner 101, xylene, mineral spirits. For personal cleanup, use soap and water.
-----------------	--

ORDERING INFORMATION

CONTACT #	1-800-888-2511
-----------	----------------

Manufacturers of Quality Protective Coatings
Esgard, Inc. . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com



SHIPPING WEIGHT

55 GAL

Varni Kote

394.0 lb (179.8kg)

FLASH POINT

Varni Kote

50°F (10°C)

SHELF LIFE

Twenty – four (24) months from date of shipment.

COLORS

Clear and black tint

CAUTION

FOR INDUSTRIAL USE ONLY! FLAMMABLE! Contains petroleum distillates.
DO NOT USE NEAR HEAT, SPARKS, OR FLAMES. Close container after use.

SAFETY

Refer to Material Safety Data Sheet supplied with each order.

FIRST AID

Refer to Material Safety Data Sheet supplied with each order.

Manufacturers of Quality Protective Coatings
Esgard, Inc . 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgardcoatings.com