



## ENVIROGARD WIRE ROPE & CABLE DRESSING

*Environmentally Friendly and Non – Toxic Wire Rope Lubricant*

<b>DESCRIPTION</b>	<p><i>Esgard EnviroGard Wire Rope &amp; Cable Dressing</i> is an <b>environmentally friendly</b> wire rope and cable dressing specifically designed to significantly extend the life of wire rope and cable while remaining non – toxic to aquatic life. <i>Esgard EnviroGard</i> was formulated to Esgard's high standards, specifically lubrication against wear, displacing moisture, resisting washout by penetrating the cable, and preventing rust and corrosion, all with no negative environmental impact which allows it fit for use in environmentally sensitive and protected areas. <i>Esgard EnviroGard</i> contains no solvents, requires no heating for application, and will not dry out or crack with age. <i>Esgard EnviroGard does not produce a sheen when immersed or negatively impact the environment.</i> <i>Esgard EnviroGard</i> performs at the upper end of specialty, high performance greases/grease-like products.</p>
<b>FIELD OF APPLICATION</b>	All new construction and field service application of wire ropes of all types, anchor lines. pendant lines. auv wires. cranes.

### TECHNICAL DATA

---

**ENVIRONMENTAL IMPACT** *Poses minimal environmental risk and is non-toxic to marine organisms.*  
(ASTM E 729-96a) *Test Duration – 96 hr. Test Specimens – Juvenile Mysid shrimp.*

---

<b>TYPE</b>	Non – toxic/Rust- inhibitive.	<b>DENSITY</b>	13.6 lb/gal (1.63 kg/l)
<b>VISCOSITY</b>	NLGI Grade 2 (Two)	<b>CONE PENETRATION</b>	269 mm
<b>TEXTURE</b>	Creamy and smooth	<b>VOLUME SOLIDS</b>	99.97%
<b>FLASH POINT</b>	294°F (145.5°C)	<b>VOLATILE MATTER</b>	<b>0.03%</b>
<b>DROPPING POINT</b>	> 550°F (288°C)	<b>SALT FOG</b> (ASTM B117)	Pass (5000 hrs)
<b>LOAD WEAR INDEX</b> (ASTM 2596)	91.2	<b>WELD LOAD</b>	500 kg

---

**APPLICATION** Apply by swabbing, brushing, or under pressure through a wire rope lubricator. Contact **Esgard** for specific lubricator recommendations. **EnviroGard** comes ready to use. Do not thin or dilute.

*Manufacturers of Quality Protective Coatings*  
Esgard, Inc. 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.  
(337)234-6327 Fax (337) 234-0113 1-800-888-2511

[www.esgardcoatings.com](http://www.esgardcoatings.com)



**ORDERING  
INFORMATION**

CONTACT # 1-800-888-2511

SHIPPING WEIGHT	<u>5 GAL</u>	<u>55 GAL</u>
<i>Esgard EnviroGard</i>	71.0 lb (32.36 kg)	727.0 lb (330.8 kg)

FLASH POINT *Esgard EnviroGard* 294°F (145.5°C) COC

SHELF LIFE Two (2) years from date of shipment.

**CAUTION** **FOR INDUSTRIAL USE ONLY!** Contains petroleum oils. **DO NOT USE OR STORE NEAR HEAT, SPARKS OR FLAMES.** Close container after use.

**SAFETY/FIRST AID** Refer to Material Safety Data Sheet supplied with each order.